

Wire for Cold Forming	
Wire Diameter	1,60 mm – 22,00 mm
Quality Standard	EN 10263-2, EN 10263-3, EN 10263-4
Packing	<ul style="list-style-type: none"> • On catch weight coils between 75-750 kg upon customer request • On steel carriers between 150-500 kg
Industries	Automotive, White Goods, Furniture, Defense, Construction, Machinery Accessory etc.

High Carbon Wire	
Wire Diameter	0,20 mm – 12,00 mm
Quality Standard	EN 10270-1, DIN 17223, ASTM A227, ASTM A228 etc.
Packing	<ul style="list-style-type: none"> • On catch weight coils between 15-750 kg upon customer request • On Z2 cardboard coils between 250-500 kg • On Z3 cardboard coils between 500-1000 kg • On K355 plastic spools about 40 kg • On wooden reels between 80-300 kg upon customer request • On steel reels between 200-450 kg upon customer request
Industries	Automotive, White Goods, Furniture, Construction, Machinery Accessory, Agriculture, Spring Manufacturing etc.

Copper Coated Low Carbon Wire	
Wire Diameter	0,50 mm – 2,50 mm
Steel Grade	SAE 1006,C4,SG2 etc.
Quality Standard	-
Packing	<ul style="list-style-type: none"> • On catch weight coils between 15-50 kg upon customer request • On Z2 cardboard coils between 250-500 kg • On wooden reels between 80-300 kg upon customer request • On steel reels between 200-450 kg upon customer request
Industries	Nail Manufacturing, Furniture, Construction, Food, Medical , Consumer Goods etc.

Copper Coated High Carbon Wire	
Wire Diameter	0,50 mm – 2,50 mm
Quality Standard	EN 10270-1, DIN17223, ASTM A227, ASTM A228 etc.
Packing	<ul style="list-style-type: none"> • On catch weight coils about 50 kg • On Z2 cardboard coils between 250-500 kg • On wooden reels between 80-300 kg upon customer request • On steel reels between 200-450 kg upon customer request
Industries	Automotive, White Goods, Defense, Medical, Consumer Goods, Spring Manufacturing etc.

Zinc Coated Low Carbon Wire	
Wire Diameter	0,13-4,50 mm
Steel Grade	SAE1006
Quality Standard	-
Packing	<ul style="list-style-type: none"> • On catch weight coils between 20-200 kg upon customer request • On Z2 cardboard coils between 250-500 kg • On Z3 cardboard coils between 500-1000 kg • On K200/K355 plastic spools about 15/40 kg • On wooden reels between 80-300 kg upon customer request • On steel reels between 200-450 kg upon customer request
Industries	Automotive, White Goods, Consumer Goods, Filters, Textile etc.

Zinc Coated High Carbon Wire	
Wire Diameter	0,60-4,50 mm
Quality Standard	EN 10270-1, DIN17223, ASTM A227, ASTM A228 etc.
Packing	<ul style="list-style-type: none"> • On catch weight coils between 20-200 kg upon customer request • On Z2 cardboard coils between 250-500 kg • On Z3 cardboard coils between 500-1000 kg • On K200/K355 plastic spools about 15/40 kg • On wooden reels between 80-300 kg upon customer request • On steel reels between 200-450 kg upon customer request
Industries	Automotive, White Goods, Defense, Food, Electric and Electronics, Textile Spring Manufacturing, Agriculture etc.

Tin Coated High Carbon Wire(White Bright)	
Wire Diameter	0,50 mm – 2,50 mm
Quality Standard	EN 10270-1, DIN17223, ASTM A227, ASTM A228 etc.
Packing	<ul style="list-style-type: none"> • On catch weight coils between 40-60 kg upon customer request • On Z2 cardboard coils between 250-500 kg • On wooden reels between 80-300 kg upon customer request • On steel reels between 200-450 kg upon customer request
Industries	Automotive, White Goods, Defense, Medical, Consumer Goods, Spring Manufacturing etc.

