

# Steam Sterilizer





# **Steam Sterilizer**

#### **General Features**

High Quality Stainless Steel (316 or 304 AISI), Used in hospitals, laboratories, prosthetics manufacturers, dental and veterinary, Ergonomic design for easier and safer loading unloading operations, In-built Steam Generator, Easy one side access for service and maintenance.

#### Safe and Sound

With security measures that protect the operator and the device,
Emergency stop button,
Sensors against obstructions on the doors pathway,
Doors locks under pressure,
Unable to open both doors at once in
Septic-Aseptic models.

#### **Control and Observe**

Every step on a handy 7" Touchscreen and PLC, Full-automatic programs, adjustable for specific calibrations, Numeric and graphic display, Integrated 40-character thermal printer, Visual, written and audial warning systems, Data storage of up 1000 cycles, USB port for transferring saved data to other media, Communications via RS 232 and RS485 Ethernet Module, 4 Analogue Manometers.



# **Quality Without Compromise**

Is our motto and we manufacture our devices assuring their quality in compliance with;

Medical Device Directive:

93/42/EEC as amended by directive 2007/47/EC

Device Classification:

Class IIb, acc. To EC MDD (Annex II)

Low Voltage Directive:

EN 60601-2-040

**EMC Directive:** 

EN 60601-1-2

Pressure Equipment Directive:

EN 13445 (Pressure Vessels)

Sterilization – Steam sterilizers – Large sterilizers: **EN285** 

Quality Management System Requirements:

EN - ISO 9001

Medical Devices – Quality management systems – Requirements for regulatory purposes:

ISO 13485

Environmental Management Systems – Requirements with guidance for use:

ISO 14001

# **Capacity and Dimensions**

Model	Chamber (WxHxD) -mm			Litres	Overall (WxHxD) - mm		
SMB-VD-75	400	400	625	100	870	1650	950
SMB-DSD-160	400	400	1000	160	870	1650	1310
SMB-DSD-200	500	500	800	200	970	1750	1110
SMB-DSD-250	500	500	1000	250	970	1750	1310
SMB-DSD-300A	500	500	1200	300	970	970	1510
SMB-DSD-300	670	670	815	377	1140	1900	1125
SMB-DSD-450	670	670	1000	450	1140	1900	1410
SMB-DSD-540	670	670	1300	580	1140	1900	1610
SMB-DSD-675	670	670	1600	715	1140	1900	1910
SMB-DSD-810	670	670	1900	850	1140	1900	2210
SMB-DSD-945	670	670	2200	985	1140	1900	2510

<sup>\*</sup> Single / Double Automatic Vertical Sliding Door System options are available.

As the main manufacturer of STERILMED Products, besides Standard STERILMED Model products and designs, visual changes can be made on a project-specific basis.





















# **Steam Sterilizer Equipments**



### **Inner Trolley**

Grid type loading rack for ISO standard baskets.

Flexibility in height adjustment of the levels maximize load capacity.

Compability with ISO standard storage shelves systems.























# Versatility

Of our devices makes room for a variety of additional eatures and accessories such as:







Computer Connection Software



er Heat on Exchanger



Ethernet Connection



AISI 304L/316L Stainless Steel Water Tank



Coded Isolation for Inactive (Cold) Pipes



Auto Release for Steam Generator



AISI 316 L Stainless Steel Pipeline and Valves



Manual Release Valve for Jacket and Chamber



Connection to Central Steam System



Ink Printer



## For a Green Future



As Sterilmed Medical, we want to leave a green future for next generations and we manufacture our products with that sensibility; a zero waste mentality. All materials used in manufacturing our devices are recyclable or eco-friendly and we constantly work on increasing the efficiency of devices for less water and energy consumption.





18. Cadde No.43 Malıköy, info@sterilmed.com.tr Sincan, Ankara/Türkiye www.sterilmed.com.tr

Başkent O.S.B. | +90 312 375 81 00